

ステンレス製 スリット排水化粧蓋

用途	目地材質	目地ピッチ mm	スキマ mm	充填深さ mm	適用荷重	型 式		ページ	みぞ幅・ます穴□ mm									
							ボルト固定仕様		150	200	250	300	350	400	450	500	600	
側溝蓋	ステンレス製	10 (15)	6 (11)	一般用	32 歩道用	LPSL10(15)-歩	LPSLB10-歩	3-2-4	●	●	●	●						
						LPSL10(15)-歩片目地	LPSLB10-歩片目地	3-2-6	●	●	●	●						
					31 T-2用	LPSL10(15)-2	LPSLB10-2	3-2-4	●	●	●	●						
						LPSL10(15)-2片目地	LPSLB10-2片目地	3-2-6	●	●	●	●						
					31 T-14 (R5) 用	LPSL10(15)-14	LPSLB10-14	3-2-4	●	●	●	●						
						LPSL10(15)-14片目地	LPSLB10-14片目地	3-2-6	●	●	●	●						
		10 (15)	6 (11)	厚物用	64 歩道用	LPSL10(15)-歩H7	LPSLB10-歩H7	3-2-5	●	●	●	●						
						LPSL10(15)-歩H7片目地	LPSLB10-歩H7片目地	3-2-7	●	●	●	●						
					63 T-2用	LPSL10(15)-2H7	LPSLB10-2H7	3-2-5	●	●	●	●						
						LPSL10(15)-2H7片目地	LPSLB10-2H7片目地	3-2-7	●	●	●	●						
					63 T-14 (R5) 用	LPSL10(15)-14H7	LPSLB10-14H7	3-2-5	●	●	●	●						
						LPSL10(15)-14H7片目地	LPSLB10-14H7片目地	3-2-7	●	●	●	●						
ます蓋	ステンレス製	10 (15)	6 (11)	一般用	32 歩道用	LPSLM10(15)-歩	LPSLMB10-歩	3-2-4				●	●		●	●	●	
						LPSLM10(15)-歩片目地	LPSLMB10-歩片目地	3-2-6				●	●		●	●	●	
					31 T-2用	LPSLM10(15)-2	LPSLMB10-2	3-2-4				●	●		●	●	●	
						LPSLM10(15)-2片目地	LPSLMB10-2片目地	3-2-6				●	●		●	●	●	
					31 T-14 (R5) 用	LPSLM10(15)-14	LPSLMB10-14	3-2-4				●	●		●	●	●	
						LPSLM10(15)-14片目地	LPSLMB10-14片目地	3-2-6				●	●		●	●	●	
		10 (15)	6 (11)	厚物用	64 歩道用	LPSLM10(15)-歩H7	LPSLMB10-歩H7	3-2-5				●	●		●	●	●	
						LPSLM10(15)-歩H7片目地	LPSLMB10-歩H7片目地	3-2-7				●	●		●	●	●	
					63 T-2用	LPSLM10(15)-2H7	LPSLMB10-2H7	3-2-5				●	●		●	●	●	
						LPSLM10(15)-2H7片目地	LPSLMB10-2H7片目地	3-2-7				●	●		●	●	●	
					63 T-14 (R5) 用	LPSLM10(15)-14H7	LPSLMB10-14H7	3-2-5				●	●		●	●	●	
						LPSLM10(15)-14H7片目地	LPSLMB10-14H7片目地	3-2-7				●	●		●	●	●	

3-2

スリット排水化粧蓋

スチール製 スリット排水化粧蓋

用 途	目地材質	目地ピッチ mm	スキマ mm	充填深さ mm		適用荷重	型 式	ページ	みぞ幅・ます穴□ℓ mm									
									150	200	250	300	350	400	450	500	600	
側溝蓋	スチール製	10.5	6	一般用	30.0	歩道用	GNSL-歩	3-2-14	●	●	●	●						
						T-2用	GNSL-2		●	●	●	●						
						T-14 (R5) 用	GNSL-14		●	●	●	●						
				厚物用	65.0	歩道用	GNSL-歩H7	3-2-16	●	●	●	●						
						T-2用	GNSL-2H7		●	●	●	●						
						T-14 (R5) 用	GNSL-14H7		●	●	●	●						
ます蓋	スチール製	10.5	6	一般用	30.0	歩道用	GNSLM-歩	3-2-15				●	●	●	●	●	●	
						T-2用	GNSLM-2					●	●	●	●	●	●	
						T-14 (R5) 用	GNSLM-14					●	●	●	●	●	●	
				厚物用	65.0	歩道用	GNSLM-歩H7	3-2-17				●	●	●	●	●	●	
						T-2用	GNSLM-2H7					●	●	●	●	●	●	
						T-14 (R5) 用	GNSLM-14H7					●	●	●	●	●	●	

スチール製 化粧蓋

用 途	目地材質			充填深さ mm		適用荷重	型 式	ページ	みぞ幅・ます穴□ ℓ mm									
				150	200				250	300	350	400	450	500	600			
側溝蓋	スチール製			一般用	30.0	歩道用	GNSLP-歩	3-2-18	●	●	●	●						
						T-2用	GNSLP-2		●	●	●	●						
						T-14 (R5) 用	GNSLP-14		●	●	●	●						
				厚物用	65.0	歩道用	GNSLP-歩H7	3-2-20	●	●	●	●						
						T-2用	GNSLP-2H7		●	●	●	●						
						T-14 (R5) 用	GNSLP-14H7		●	●	●	●						
ます蓋	スチール製			一般用	30.0	歩道用	GNSLMP-歩	3-2-19				●	●	●	●	●	●	
						T-2用	GNSLMP-2					●	●	●	●	●	●	
						T-14 (R5) 用	GNSLMP-14					●	●	●	●	●	●	
				厚物用	65.0	歩道用	GNSLMP-歩H7	3-2-21				●	●	●	●	●	●	
						T-2用	GNSLMP-2H7					●	●	●	●	●	●	
						T-14 (R5) 用	GNSLMP-14H7					●	●	●	●	●	●	

鋳鉄製 スリット排水化粧蓋

用 途	目地材質		スキマ mm	充填深さ mm		適用荷重	型 式	ページ	みぞ幅・ます穴□ℓ mm												
									150	200	250	300	350	400	450	500	600				
側溝蓋	鋳鉄製		5.9	厚物用	50	T-2用	DGSL-40-2H5	3-1-26				●									
						T-14 (R5) 用	DGSL-40-14H5					●									
					71	T-2用	DGSL-40-2H7					●									
						T-14 (R5) 用	DGSL-40-14H7					●									
						6.5	一般用		36	T-2用	DGSL-2	3-1-28	●	●	●	●					
										T-14 (R5) 用	DGSL-14		●	●	●	●					
T-2用	DGSLM-2				●																
T-14 (R5) 用	DGSLM-14				●						●		●								
ます蓋	鋳鉄製																				