

たて口排水用、よこ口排水用ドレイン 全機種 スペーサー 一覧表

2021年6月21日 管理番号：RD1-2106216 製品分類：ルーフドレイン

第一機材株式会社

打込金具 スペーサーの規格及び寸法一覧となります。

◆たて口排水用 打込金具一覧表

型式記号	呼称	スペーサーの規格 (mm)			
		種類	内径	外径	長さ
RVW RVW-P	50	SU100	100	106	H1 - 50
	65	SU100	100	106	H1 - 50
	75	VU100	107	114	H1 - 50
	100	VU125	131	140	H1 - 50
	125	VU150	154	165	H1 - 50
	150	VU200	202	216	H1 - 55
	200	スフェス	234	236	H1 - 60
RV RV-P	50	VU75	83	89	H1 - 60
	65	SU100	100	106	H1 - 60
	75	VU100	107	114	H1 - 60
	100	VU125	131	140	H1 - 60
	125	VU150	154	165	H1 - 60
	150	VU200	202	216	H1 - 40
RA-M RA-M-P	50	SU75	75	80	H1 - 40
	65	VU75	83	89	H1 - 40
	75	SU100	100	106	H1 - 40
	100	SU125	125	134	H1 - 40
	125	VU150	154	165	H1 - 40
RVE RVE-P	50	VU75	83	89	H1 - 40
	65	SU100	100	106	H1 - 40
	75	VU100	107	114	H1 - 40
	100	VU125	131	140	H1 - 40
	125	VU150	154	165	H1 - 40
	150	VU200	202	216	H1 - 40
RAE RAE-P	50	VU75	83	89	H1 - 30
	65	SU100	100	106	H1 - 30
	75	VU100	107	114	H1 - 30
	100	VU125	131	140	H1 - 30
	125	VU150	154	165	H1 - 30
	150	VU200	202	216	H1 - 30
RFBM	50	VU75	83	89	H1 - 35
	65	VU75	83	89	H1 - 35
	75	SU100	100	106	H1 - 35
	100	SU125	125	134	H1 - 35
	125	VU150	154	165	H1 - 35
	150	VU200	202	216	H1 - 30
RP RPE	50	VU75	83	89	H1 - 60
	65	SU100	100	106	H1 - 60
	75	VU100	107	114	H1 - 60
	100	VU125	131	140	H1 - 60
	125	VU150	154	165	H1 - 60
	150	VU200	202	216	H1 - 40
RKM RKEM	50	SU75	75	80	H1 - 25
	65	VU75	83	89	H1 - 25
	75	SU100	100	106	H1 - 25
	100	SU125	125	134	H1 - 25
	125	VU150	154	165	H1 - 25
RT	50	SUC75	75	80	H1 - 60
	75	SUC100	100	106	H1 - 60
RSM	50	SUC75	75	80	H1 - 30
	75	SUC100	100	106	H1 - 30

型式記号	呼称	スペーサーの規格 (mm)			
		種類	内径	外径	長さ
RVW-DR					
	75	VU100	107	114	H1 - 50
	100	VU125	131	140	H1 - 50
	125	VU150	154	165	H1 - 50
	150	VU200	202	216	H1 - 55
RV-DR	50	VU75	83	89	H1 - 60
	65	SU100	100	106	H1 - 60
	75	VU100	107	114	H1 - 60
	100	VU125	131	140	H1 - 60
	125	VU150	154	165	H1 - 60
	150	VU200	202	216	H1 - 40
RA-M-DR	50	SU75	75	80	H1 - 40
	65	VU75	83	89	H1 - 40
	75	SU100	100	106	H1 - 40
	100	SU125	125	134	H1 - 40
	125	VU150	154	165	H1 - 40
RVE-DR	50	VU75	83	89	H1 - 40
	65	SU100	100	106	H1 - 40
	75	VU100	107	114	H1 - 40
	100	VU125	131	140	H1 - 40
	125	VU150	154	165	H1 - 40
	150	VU200	202	216	H1 - 40
RAE-DR	50	VU75	83	89	H1 - 30
	65	SU100	100	106	H1 - 30
	75	VU100	107	114	H1 - 30
	100	VU125	131	140	H1 - 30
	125	VU150	154	165	H1 - 30
	150	VU200	202	216	H1 - 30
RFBM-DR	50	VU75	83	89	H1 - 35
	65	VU75	83	89	H1 - 35
	75	SU100	100	106	H1 - 35
	100	SU125	125	134	H1 - 35
	125	VU150	154	165	H1 - 35
	150	VU200	202	216	H1 - 30
RP-DR RPE-DR	50	VU75	83	89	H1 - 60
	65	SU100	100	106	H1 - 60
	75	VU100	107	114	H1 - 60
	100	VU125	131	140	H1 - 60
	125	VU150	154	165	H1 - 60
	150	VU200	202	216	H1 - 40
RKM-DR RKEM-DR	50	SU75	75	80	H1 - 25
	65	VU75	83	89	H1 - 25
	75	SU100	100	106	H1 - 25
	100	SU125	125	134	H1 - 25
	125	VU150	154	165	H1 - 25
RT-DR	50	SUC75	75	80	H1 - 60
	75	SUC100	100	106	H1 - 60
RSM-DR	50	SUC75	75	80	H1 - 30
	75	SUC100	100	106	H1 - 30

型式記号	呼称	スペーサーの規格 (mm)			
		種類	内径	外径	長さ
RS2DM	75	SUC100	100	106	H1 - 35
	50	SUC75	75	80	H1 - 30
	75	SUC100	100	106	H1 - 30
RTE	50	SUC75	75	80	H1 - 30
RSEM	75	SUC100	100	106	H1 - 30
RSLV	50	SUC75	75	80	H1 - 80
	75	SUC100	100	106	H1 - 80
RSLM	50	SUC75	75	80	H1 - 70
RSLM2	75	SUC100	100	106	H1 - 40
	100	SUC125	125	134	H1 - 40
BFV	75	SUC100	100	106	H1 - 60
	100	SUC125	125	134	H1 - 60
BF-M	50	SU75	75	80	H1 - 45
BFF-M	75	SUC100	100	106	H1 - 35
	100	SUC125	125	134	H1 - 35
	125	VUC150	154	165	H1 - 35
BF2-M	75	SU100	100	106	H1 - 45
	100	SU125	125	134	H1 - 45

型式記号	呼称	スペーサーの規格 (mm)			
		種類	内径	外径	長さ
SRA-1	50	VU75	83	89	H1 - 60
	75	VU100	107	114	H1 - 60
	100	VU125	131	140	H1 - 60
	125	VU150	154	165	H1 - 60
	150	VU200	202	216	H1 - 40
SRA-2	50	VU75	83	89	H1 - 40
	75	VU100	107	114	H1 - 40
	100	VU125	131	140	H1 - 40
	125	VU150	154	165	H1 - 40
SRV	50	VU75	83	89	H1 - 30
	75	VU100	107	114	H1 - 30
	100	VU125	131	140	H1 - 30
SRA	50	VU75	83	89	H1 - 30
	75	VU100	107	114	H1 - 30
	100	VU125	131	140	H1 - 30
SRM-1	50	VU75	83	89	H1 - 60
	75	VU100	107	114	H1 - 60
	100	VU125	131	140	H1 - 60
SRM-2	50	VU75	83	89	H1 - 30
	75	VU100	107	114	H1 - 30
	100	VU125	131	140	H1 - 30

◆よこ口排水用 打込金具一覧表

型式記号	呼称	スペーサーの規格 (mm)			
		種類	内径	外径	長さ
RL-W RL-W-P	75	SU100	100	106	H1 - 50
	100	SU125	125	134	H1 - 55
	125	VU150	154	165	H1 - 55
	150	LP180	180	186	H1 - 55
	200	スチール	234	236	H1 - 60
RL-4S RL-4SP	50	VU65	71	76	H1 - 30
	65	VU75	83	89	H1 - 35
	75	SU100	100	106	H1 - 40
	100	SU125	125	134	H1 - 45
	125	VU150	154	165	H1 - 50
RL-5A RL-5M RL-5ADP	150	LP180	180	186	H1 - 50
	50	VU65	71	76	H1 - 35
	65	VU75	83	89	H1 - 40
	75	SU100	100	106	H1 - 40
	100	SU125	125	134	H1 - 45
RL-7ML	125	VU150	154	165	H1 - 45
	150	LP180	180	186	H1 - 45
	50	VU65	71	76	H1 - 40
RL-M	75	SU100	100	106	H1 - 45
	50	VU65	71	76	H1 - 30
	65	VU75	83	89	H1 - 35
	75	SU100	100	106	H1 - 40
	100	SU125	125	134	H1 - 45
RL-M	125	VU150	154	165	H1 - 50

型式記号	呼称	スペーサーの規格 (mm)			
		種類	内径	外径	長さ
SR-A	50	VU65	71	76	H1 - 30
	75	SU100	100	106	H1 - 40
	100	SU125	125	134	H1 - 45
	125	VU150	154	165	H1 - 50
	150	LP180	180	186	H1 - 50
SR-M	50	VU65	71	76	H1 - 30
	75	SU100	100	106	H1 - 40
	100	SU125	125	134	H1 - 45
	125	VU150	154	165	H1 - 50