

## 化粧蓋 質量表【単体質量・(参考)仕上材充填蓋質量】

2022年10月3日 管理番号 : MC1-2210031D 製品分類 : マンホールカバー (2026/2/5 修正)

第一機材株式会社

2026年2月5日現在の質量となります。

単位:kg					
型式	寸法	蓋質量	受枠質量	1組質量	仕上材充填蓋質量
MT-H2S	300	12.7	12.4	25.1	約25.0
	350	14.9	14.2	29.1	約31.0
	450	16.9	20.1	37.0	約42.0
	600	25.2	25.7	50.9	約70.0
MT-H6S	300	12.7	12.4	25.1	約25.0
	350	14.9	14.2	29.1	約31.0
	450	22.9	20.1	43.0	約48.0
	600	39.6	25.7	65.3	約84.0
MT-HDS	300	12.7	12.4	25.1	約25.0
	350	14.9	14.2	29.1	約31.0
	450	22.9	20.1	43.0	約48.0
	600	39.6	25.7	65.3	約84.0
MT-H2SL	300	12.7	12.5	25.2	約25.0
	350	14.9	14.3	29.2	約31.0
	450	18.2	20.2	38.4	約43.0
	600	26.5	25.8	52.3	約71.0
MT-H6SL	300	12.7	12.5	25.2	約25.0
	350	14.9	14.3	29.2	約31.0
	450	24.2	20.2	44.4	約49.0
	600	40.9	25.8	66.7	約85.0
MT-HDSL	300	12.7	12.5	25.2	約25.0
	350	14.9	14.3	29.2	約31.0
	450	24.2	20.2	44.4	約49.0
	600	40.9	25.8	66.7	約85.0
MT-E2	300	12.3	11.7	24.0	約24.0
	350	14.5	13.4	27.9	約29.0
	450	20.7	16.3	37.0	約45.0
	600	23.7	25.2	48.9	約68.0
MT-E6	300	12.3	11.7	24.0	約24.0
	350	14.5	13.4	27.9	約29.0
	450	20.7	16.3	37.0	約45.0
	600	36.7	25.2	61.9	約81.0
MT-ED	300	12.3	11.7	24.0	約24.0
	350	14.5	13.4	27.9	約29.0
	450	20.7	16.3	37.0	約45.0
	600	36.7	25.2	61.9	約81.0

単位:kg					
型式	寸法	蓋質量	受枠質量	1組質量	仕上材充填蓋質量
MT-E2L	300	12.3	11.8	24.1	約24.0
	350	14.5	13.5	28.0	約29.0
	450	20.7	16.4	37.1	約45.0
	600	25.0	25.3	50.3	約69.0
MT-E6L	300	12.3	11.8	24.1	約24.0
	350	14.5	13.5	28.0	約29.0
	450	20.7	16.4	37.1	約45.0
	600	38.0	25.3	63.3	約82.0
MT-EDL	300	12.3	11.8	24.1	約24.0
	350	14.5	13.5	28.0	約29.0
	450	20.7	16.4	37.1	約45.0
	600	38.0	25.3	63.3	約82.0
MT-5S	300	7.2	6.8	14.0	約13.0
	350	8.7	8.2	16.9	約17.0
	450	14.0	11.7	25.7	約29.0
	500	15.9	12.7	28.6	約34.0
	600	22.8	15.3	38.1	約49.0
	750	60.2	27.1	87.3	約120.0
MT-5S6	600	30.3	16.3	46.6	約55.0
MT-5SD	450	14.0	11.6	25.6	約29.0
	600	23.5	15.4	38.9	約51.0
MWPT-5S	600	上蓋 中蓋	22.8 22.3	44.9	90.0
	750	上蓋 中蓋	60.2 23.8	56.0	140.0
	600	上蓋 中蓋	14.6 10.4	25.0	50.0
	600	上蓋 中蓋	22.3 74.2	89.8	197.0
MWPT-3S	450	22.3	23.1	45.4	約48.0
	600	32.8	31.7	64.5	約74.0
MT-24DS	600	33.0	34.6	67.6	約67.0
	900	中蓋 外蓋	33.0 74.2	89.8	197.0
	600	33.0	26.1	59.1	約67.0
MT-14K	900	中蓋 外蓋	33.0 74.2	70.8	178.0
	600	33.0	26.1	59.1	約67.0
	900	中蓋 外蓋	33.0 74.2	70.8	178.0
MT-14KD	600	33.0	26.1	59.1	約67.0
	900	中蓋 外蓋	33.0 74.2	70.8	178.0
MT-14	600	33.0	26.1	59.1	約67.0
	900	中蓋 外蓋	33.0 74.2	70.8	178.0
MT-14D	600	33.0	26.1	59.1	約67.0
	900	中蓋 外蓋	33.0 74.2	70.8	178.0

單位:kg

單位:kg

型式	寸法	蓋質量	受桿質量	1組質量	仕上材充填 蓋質量
MT-24P	300	10.8	12.2	23.0	約27.0
	450	17.3	16.0	33.3	約43.0
	500	22.4	17.2	39.6	約54.0
	600	27.7	19.8	47.5	約73.0
MIB-14	450	24.0	23.5	47.5	約50.0
	500	27.9	26.9	54.8	約61.0
	600	40.8	72.2	113.0	約83.0
	750	50.0	131.5	181.5	約117.0
MIB-14D	450	24.0	23.5	47.5	約50.0
	500	27.9	26.9	54.8	約61.0
	600	54.4	73.6	128.0	約97.0
	750	80.0	142.0	222.0	約147.0
MIB-RS-2	450	21.6	25.8	47.4	約53.0
	600	31.2	33.6	64.8	約84.0
MIB-RS-6	450	21.6	25.8	47.4	約53.0
	600	31.2	33.6	64.8	約84.0
MIB-RS-14	450	22.8	25.8	48.6	約54.0
	600	33.8	33.6	67.4	約87.0
MIB-RS-20	450	24.2	26.8	51.0	約55.0
	600	37.2	34.8	72.0	約90.0
MIB-R2-2	450	21.6	24.8	46.4	約53.0
	600	31.2	32.6	63.8	約84.0
MIB-R2-6	450	21.6	24.8	46.4	約53.0
	600	31.2	32.6	63.8	約84.0
MIB-R2-14	450	22.8	24.8	47.6	約54.0
	600	33.8	32.6	66.4	約87.0
MIB-R2-20	450	24.2	25.8	50.0	約55.0
	600	37.2	33.8	71.0	約90.0
MIB-R2-20-OS	300	6.6	5.2	11.8	約9.5
	450	40.8	25.8	66.6	約65.2
	600	59.1	33.8	92.9	約104.6
MTIB-20SL	900	130.2	92.0	222.2	約295.8
MTIB-20L	900	127.6	89.6	217.2	約293.2

型式	寸法	蓋質量	受桿質量	1組質量	仕上材充填 蓋質量
MIB-2 MIB-2-Y	300	11.4	19.8	31.2	約30.0
	350	15.7	23.3	39.0	約36.0
	450	19.0	32.2	51.2	約59.0
	500	25.1	35.1	60.2	約73.0
	600	36.6	44.0	80.6	約103.0
MIB-6 MIB-6-Y	300	16.2	19.8	36.0	約33.0
	350	18.7	23.3	42.0	約42.0
	450	26.5	32.2	58.7	約65.0
	500	35.6	35.1	70.7	約82.7
	600	46.0	44.0	90.0	約112.0
MIB-D MIB-D-Y	300	11.4	19.8	31.2	約30.0
	350	15.7	23.3	39.0	約41.0
	450	23.5	32.2	55.7	約62.0
	500	25.1	35.1	60.2	約73.0
	600	36.0	44.0	80.0	約104.0
MIB-D	750	29.2 × 2個	78.7	137.1	約79.0 × 2個
	900	46.7 × 2個	98.7	192.1	約116.0 × 2個
MIB-20D MIB-20D-Y	300	16.2	19.8	36.0	約33.0
	350	18.7	23.3	42.0	約42.0
	450	26.5	32.2	58.7	約65.0
	500	35.6	35.1	70.7	約82.7
	600	46.0	44.0	90.0	約112.0
MIB-2S	300	11.9	20.7	32.6	約31.0
	350	16.2	24.4	40.6	約37.0
	450	19.7	33.5	53.2	約61.0
	500	26.0	36.5	62.5	約74.0
	600	37.6	45.6	83.2	約105.0
MIB-6S	300	16.7	20.7	37.4	約34.0
	350	19.2	24.4	43.6	約43.0
	450	27.2	33.5	60.7	約66.0
	500	37.0	36.5	73.5	約84.3
	600	47.0	45.6	92.6	約114.0
MIB-DS	300	11.9	20.7	32.6	約31.0
	350	16.2	24.4	40.6	約42.0
	450	24.2	33.5	57.7	約63.0
	500	26.0	36.5	62.5	約74.0
	600	37.0	45.6	82.6	約106.0
	750	30.3 × 2個	80.8	141.4	約80.0 × 2個
	900	48.0 × 2個	101.2	197.2	約117.0 × 2個

單位:kg

型式	寸法	蓋質量	受桿質量	1組質量	仕上材充填 蓋質量
MHIB-6	450	26.0	22.0	48.0	約63.0
	600	40.0	31.0	71.0	約107.0
MHIB-20	450	29.0	22.0	51.0	約65.5
	600	48.0	31.0	79.0	約115.0
MHIB-6S	450	27.1	22.0	49.1	約65.8
	600	41.2	31.0	72.2	約108.2
MHIB-20S	450	30.1	22.0	52.1	約68.3
	600	49.2	31.0	80.2	約116.2
MIBE-6	300	13.1	13.0	26.1	約29.4
	350	15.1	17.4	32.5	約39.7
MIB-20	300	14.6	13.0	27.6	約30.4
	350	16.2	17.4	33.6	約40.8
MIBE-6S	300	14.2	13.0	27.2	約31.4
	350	15.8	17.4	33.2	約40.4
MIBE-20S	300	15.7	13.0	28.7	約32.4
	350	16.9	17.4	34.3	約41.5
MIB-R	600	30.0	37.0	67.0	約82.0
MIB-RD	600	38.9	33.8	72.7	約84.0
MWT-22DS	600	38.1	32.2	70.3	約81.0
MWT-22D	900	79.8	66.2	146.0	約197.0
	350	14.9	16.8	31.7	約31.0
MT-22P	450	21.9	22.2	44.1	約47.0
	600	36.2	25.0	61.2	約79.0
MIB-D5	36.0×5個	195.0	375.0	約104.0×5個	
MIB-D4	36.0×4個	158.0	302.0	約104.0×4個	
MIB-D3	36.0×3個	120.0	228.0	約104.0×3個	
MIB-D2	36.0×2個	83.0	155.0	約104.0×2個	
MIB-D2-45	23.0×2個	64.4	110.4	約63.0×2個	
MCAB	400×800	35.0	40.0	75.0	約95.0
	600×1200	36.0×2個	85.0	157.0	約99.0×2個
	600×1350	40.0×2個	89.0	169.0	約111.0×2個
	1000×850	26.0×4個	142.0	246.0	約65.0×4個
	1000×1350	39.0×4個	172.0	328.0	約100.0×4個
	1200×1408-3	74.0×3個	97.0	319.0	約130.0×3個
	1200×1408-4	55.0×4個	109.0	329.00	約97.0×4個